

Ecran d'affichage CX-NT-MH-B 75"



Display	
Model	ND75CMB
Screen Size	75"
Aspect Ratio	16:9
Panel Type	ADS
Backlight	DLED
Pixel Pitch	0.430 (H) × 0.430 (V) mm
Display Area	1650.24 (H) × 928.26 (V) mm
Brightness (Typ.)	500 nits
Haze	25%
Resolution	3840 × 2160
Refresh Rate	60 Hz
Contrast Ratio (Typ.)	1,200:1
Viewing Angle (H × V)	178° / 178°
Color Gamut	98% sRGB
Display Orientation	Landscape / Portrait
Response Time	8 ms
Life Time (50%)	> 50,000 hours
Operation Hour (Hour / Day)	24 / 7
Display Color	1.07B (10bit)
Sensor	Ambient light sensor
Audio	
Sound Channel	2.0
Speaker Power	2 × 12W (Output) 2 × 16W (Maximum)

Built-in System	
Operating System	Android 14.0
CPU	A73 × 4, 1.8GHz
GPU	G57 MC1
APU	1.5 TOPS
RAM	4 GB
ROM	32 GB
Connectivity	
HDMI IN × 3	2.0, up to 4K@60Hz, CEC, ARC (HDMI 1)
USB 2.0 × 2	Rear: For external peripherals Side: Wireless dongle pairing, USB clone
USB 3.0 × 1	For external peripherals
Input	USB Type-C × 1 Video and audio transmission, 65W PD charging, LAN network sharing
AUDIO IN × 1	3.5mm Jack
RS232 × 1	DB-9
RJ45 IN × 1	10M / 100M / 1000Mbps
Output	HDMI OUT × 1 Up to 4K@60Hz, not supported in Android and HDMI 1 channel
AUDIO OUT × 1	3.5mm Jack
SPDIF × 1	PCM output format
RJ45 OUT × 1	10M / 100M / 1000Mbps
Wi-Fi Module Slot	Module slot × 1
Wi-Fi Module (SI07B)	Wi-Fi 6 supported 802.11ac/b/g/n/a/ax, 2.4GHz/5GHz
Bluetooth	5.2

Feature	
System OS	Signage OS V2
Screen Share	Share Support BYOD / Miracast / Airplay / Chromecast
Device Management	Pivot
Protocol Control	RS232 / IP control Compatible with control systems (Crestron, Q-SYS, and Extron)
Special Features	Screen rotation / Auto input change / Play via URL / Wake on LAN / Color Calibration

Accessory	
Power Cord	3 m × 1
HDMI Cable	3 m × 1
Remote Control	× 1
Display Bracket	× 2
Wall Mount Bracket	× 1
Wi-Fi Module	× 1

Standard	
Environment	Energy Star
IP Rating	IP5X

Physical Specification	
Bezel Width	15.9 mm / 0.63 inch (Even)
Dimension (W × H × D)	1685.6 × 963.7 × 68 mm / 66.39 × 37.95 × 2.68 inch
Shipping Dimension (W × H × D)	1863 × 1090 × 225 mm / 73.35 × 42.91 × 8.86 inch
Thickness of Machine and Wall Mount	101 mm / 3.98 inch (WIB6560A)
VESA	600 × 400 mm
Net Weight	33.22 kg / 73.24 lb
Gross Weight	48.44 kg / 106.85 lb

Environmental Conditions	
Operating Temperature	0°C ~ 40°C / 0°F ~ 104°C
Storage Temperature	-20°C ~ 60°C / -4°F ~ 140°F
Operating Humidity	10% ~ 90% RH
Storage Humidity	10%~ 90% RH
Altitude	Below 5000 m

Power	
Power Supply	100-240V~50/60Hz
Standby Power	≤ 0.5 W
Power Consumption (Typ.)	119 W
Power Consumption (Max.)	169 W

Warranty	
Display	3 years warranty

Statement

Size and weight vary by configuration and manufacturing process, please refer to the actual product. The product images are for illustrative purposes only and may slightly differ in appearance, colour, size, etc. from the actual product. The description, illustrations, etc. in this document may subject to change in accordance with the latest product specification and performance. Should the above-mentioned change in the document become necessary, the document may be updated without written notice.

